

CNC MULTI AXIS CENTER AND DRIVEN TOOLS
数控系统多轴中心和驱动工具

TECHNICAL SPECIFICATIONS 技术规格	DM-50	DM-63	DM-80
TRAVELS: 行程范围:			
Travel Distance X-axis: 行程 X 轴:	850mm	900mm	900mm
Travel Distance Z-axis: 行程 Z 轴:	700mm	800mm	800mm
Travel Distance Y-axis: 行程 Y 轴:	750mm	850mm	850mm
Travel Distance A-axis: 行程 A 轴:	±30~120 (Option 选择项目)		
Max.Speed C-axis C轴工作台旋转最高速度	50rpm-1100rpm		
Travel Distance A-axis: 行程 C 轴:	0.001mm(分割)		
CAPACITY: 容量:			
Table Working Surface	Φ 500mm	Φ 630	Φ 800mm
Table loading capacity	800kg	1100kg	1600kg
MODEL主轴型号	HSK-A63		
Spinble Speed range主轴转速	50-12000rpm		
Spinble drive motor主轴电机功率	18kw-22kw		
Spinble bearing inner diameter主轴轴承内径	Φ80mm		
Rapid traverse rate (X/Z/Y)轴进给速度	48m		
Spindle Mazagine (with ATC)刀库规格及数量			
Type of tool shank刀具形式	HSK-A63		
Max.length of tool最大刀具长度	440mm		
Tool storage capacacity刀库容量	40pcs标准 (60pcs / 80pcs Option选择配置)		
Max.diameter of tool最大刀具直径	Φ200		
Max.tool diameter in full setting刀具相邻空间	Φ80mm		
Pump discharge pressure气体输出量	7MPa		
Oil reservoir液压站容量	30L		
Tank capacity切削液容量	800L		
Oil cooling capacacity Motor andball screw brackets	100-5000W		
Electric power supply总功率	MAX.60kva	MAX.80kva	
Machine weight 机床重量	9000kg	15000kg	
Standard 配备所有标准和可选附件	X/Z/Y/A/B光栅尺		

