

**CNC MULTI AXIS CENTER WITH TWO SPINDLES, TWO TURRETS, C-AXIS, Y-AXIS AND DRIVEN TOOLS**  
**数控系统多轴中心带两个主轴、1个刀塔、C 轴、Y 轴和驱动工具**

TECHNICAL SPECIFICATIONS 技术规格	TBX-42/500SMCY	TBX-52/500SMCY
	TRAVELS: 行程范围:	TRAVELS: 行程范围:
Travel Distance X1-axis: 行程 X1 轴:	230 mm	
Travel Distance Z1-axis: 行程 Z1 轴:	500 mm	
Travel Distance X2-axis: 行程 X2 轴:	120 mm	
Travel Distance Z2-axis: 行程 Z2 轴:	220 mm	
Travel Distance Z3-axis: 行程 Z3 轴:	210mm	
Travel Distance Y1-axis: 行程 Y1 轴:	±50 mm	
<b>CAPACITY: 容量:</b>		<b>CAPACITY: 容量:</b>
Max Turning Diameter (Upper Turret): 最大旋转直径 (上刀塔):	Ø230 mm	
Max Turning Length: 最大车削长度:	500 mm	
Through Hole Diameter (Left Spindle): 通孔直径 (左主轴):	Ø42 mm	Ø52 mm
Through Hole Diameter (Right Spindle): 棒材直径 (右主轴):	Ø30 mm	
<b>SPINDLE (LEFT / RIGHT): 主轴 (左/右):</b>		<b>SPINDLE (LEFT / RIGHT): 主轴 (左/右):</b>
Speed: 速度:	5000rpm	4500rpm
Power: 功率:	7.5kW (2:1减速比)	11 kW (2:1减速比)
Torque: 扭矩:	130 Nm	190Nm
<b>Tooling: 工具:</b>		<b>Tooling: 工具:</b>
Shank: 刀塔形式:	上刀塔BMT-55/12T (下刀塔BMT-40/12T)	
Turret Stations: 刀塔刀具数量:	12-24/Turret - Live	
Boring Bar Diameter: 镗杆直径:	ER32	
Rotary Tool Speed: 旋转工具速度:	6000 rpm	
Rotary Tool Power: 旋转工具功率:	2.2 kW	
Rotary Tool Torque: 旋转工具扭矩:	19 Nm	
Kg: 机床重量:	6800kg	
With all standard and optional accessories 配备所有标准和可选附件		