

**CNC MULTI AXIS CENTER WITH TWO SPINDLES, THREE TURRETS, C-AXIS, Y-AXIS AND DRIVEN TOOLS**  
**数控系统多轴中心带两个主轴、3个刀塔、C轴、Y轴和驱动工具**

<b>TECHNICAL SPECIFICATIONS 技术规格</b>		<b>D42 Series</b>	<b>D52 Series</b>	<b>D65 Series</b>
行程范围:		<b>TRAVELS:</b> 行程范围:	<b>TRAVELS:</b> 行程范围:	<b>TRAVELS:</b> 行程范围:
One System 1系统	Travel Distance X1-axis: 行程 X1 轴:	300mm		
	Travel Distance Z1-axis: 行程 Z1 轴:	700 mm		
	Travel Distance Y1-axis: 行程 Y1 轴:	±45 mm		
Two System 2系统	Travel Distance X2-axis: 行程 X2 轴:	190mm		
	Travel Distance Z2-axis: 行程 Z2 轴:	520mm		
	Travel Distance Y2-axis: 行程 Y2 轴:	±45 mm		
Three System 3系统	Travel Distance X3-axis: 行程 X3 轴:	190mm		
	Travel Distance Y3-axis: 行程 Y3 轴:	±45 mm (Option: Y3 axis)		
Travel Distance A-axis: 行程 A 轴:		700 mm		
Travel Distance B-axis: 行程 B 轴:		+30mm -120mm (Option)		
<b>CAPACITY: 容量:</b>		<b>CAPACITY: 容量:</b>		
Max Turning Diameter (Upper Turret): 最大转弯直径 (上刀塔):		Ø500 mm (刀盘直径300mm,安装刀具后500mm)		
Max Turning Diameter (Left Right Lower Turret): 最大转弯直径 (左右下刀塔):		Ø500 mm (刀盘直径300mm,安装刀具后500mm)		
Max Turning Length: 最大车削长度:		Ø700mm (Option: Ø1250 mm)		
Through Hole Diameter (Left Spindle): 通孔直径 (左主轴):		Ø42 mm	Ø52 mm	Ø65 mm
Through Hole Diameter (Right Spindle): 通孔直径 (右主轴):		Ø30 mm	Ø42 mm	Ø52 mm
<b>SPINDLE (LEFT / RIGHT): 主轴 (左/右):</b>		<b>SPINDLE (LEFT / RIGHT): 主轴 (左/右):</b>		
Chuck Size: 卡盘尺寸:		6In or 5In	8In or 6In	8In or 6In
Speed: 速度:		4500rpm	4300rpm	4000rpm
Power: 功率:		11/7.5		
Torque: 扭矩:		116/93 Nm (86/69 ft - lbs)		
<b>Tooling: 工具:</b>		<b>Tooling: 工具:</b>		
Shank: 刀柄:		BMT-45 (Option: BMT-55)		
Turret Stations: 刀塔站:		3 x 12/Turret - Live 2 x 12/刀塔 - 现场		
Boring Bar Diameter: 镗杆直径:		25		
Rotary Tool Speed: 旋转工具速度:		6000rpm		
Rotary Tool Power: 旋转工具功率:		3.7kw		
Rotary Tool Torque: 旋转工具扭矩:		23.5Nm x3		
With all standard and optional accessories 配备所有标准和可选附件				